

Sleeveless Top Pattern and Instructions – for personal use only
for 80 cm/31.5 inch Lusion BJD from Dollmore
by Answer42

2 pieces: front, back

All seams have a ¼ inch seam allowance.

The back will overlap by about ½ inch for snaps or buttons.

The front length reaches to Lusion Dahlia's bellybutton.

Cut 1 front piece on fold and 2 back pieces (reversing/flipping 1 of the back pieces) from fabric.

Sew shoulder seams of fabric pieces.

Cut the same 3 pieces from lining fabric. Sew shoulder seams of lining pieces.

Press all shoulder seams open. Mark hem by pressing up ¼ inch hem on bottom of all pieces.

Pin fabric top to lining top, matching shoulder seams.

Pin along armholes, neckline and back seams.

Sew armholes, neckline and back seams, backstitching at beginning and end of each seam. Do not sew hems in place. Press to set seams.

Trim armhole and neckline seams to about 1/8 inch wide and clip curves.

Turn top right side out. Press.

Pin side seams together, matching underarm seams.

Sew side seams, backstitching at beginning and end of each seam. Press.

Trim side seam in armhole area to about 1/8 inch wide.

Fold under pre-pressed ¼ inch hem and topstitch hem, making sure lining does not show on outside of garment. Press.

Topstitch around neckline and armholes. Press.

Add snaps or buttons to back opening.

Embellish as desired.

Have fun!

This top is very basic. Please let your imagination loose and enjoy!

This top could become lingerie, a summer top or a bodice to a dress. If you cut the back neckline lower and put the opening in the front, you can use this pattern as a vest.

I recommend printing out this pattern before some electronic gremlin eats it for lunch.

Sleeveless Top for 80 cm Bust

by Answer42

BACK

Cut 2 of fabric
Cut 2 of lining

¼ inch seam allowance included

FRONT

Cut 1 on fold of fabric
Cut 1 on fold of lining

¼ inch seam allowance included on all sides

2 inches

place on fold

